



主要外形尺寸及连接尺寸 Key external dimensions and connection dimensions **H44H (Y, W)**

规格 Class	公称直径 DN		凸面法兰(RF)主要连接尺寸					Key connection dimension of convex flange (RF)		H44H外形尺寸	
	in	mm	L	D	D1	D2	b	f	Z-φd	H	
150Lb	2	50	283	152	120.5	92	20	1.6	4-19	165	
	2 1/2	65	216	178	139.5	105	23		4-19	175	
	3	80	241	190	152.5	127	24		4-19	190	
	4	100	292	229	190.5	157	24		8-19	215	
	5	125	356	254	216	186	24		8-22	245	
	6	150	406	279	241.5	216	25.5		8-22	265	
	8	200	493	343	298.5	270	29		8-22	320	
	10	250	622	406	362	324	39.5		12-25	365	
	12	300	698	483	432	381	32		12-25	415	
	14	350	787	533	476	413	35		12-29	460	
	16	400	914	597	540	470	37		16-29	495	
	20	450	978	697	633	584	43		20-32	590	
	24	600	1293	813	749.5	692	48		20-35	650	
	28	700	1448	927	863.5	800	71.5		28-35	705	
	300Lb	2	50	267	165	127	92		22.5	8-19	190
		2 1/2	65	292	190	149	105		25.5	8-22	205
3		80	318	210	168	127	28.5	8-22	220		
4		100	356	254	200	157	32	8-22	245		
5		125	400	279	235	186	35	8-22	275		
6		150	444.5	318	270	216	36.5	12-23	295		
8		200	559	381	330	270	41.5	12-25	330		
10		250	622	444.5	387.5	324	48	16-29	420		
12		300	711	521	451	381	51	16-32	480		
14		350	838	584	514.5	413	54	20-32	535		
16		400	864	648	571.5	470	57.5	20-35	585		
20		500	1016	778	686	584.5	63.5	24-35	685		
24		600	1304	914.5	813	692.5	70	24-41	785		

注：如法兰密封面采用凸面以外的型式，请在订货时注明。  
Note: Please specify in your purchase order if flange sealing face uses types other than convex.

01000000000000000000

01000000000000000000

主要外形尺寸及连接尺寸 Key external dimensions and connection dimensions **H44H (Y, W)**

规格 Class	公称直径 DN		凸面法兰(RF)主要连接尺寸					Key connection dimension of convex flange (RF)		H44H外形尺寸	
	in	mm	L	D	D1	D2	b	f	Z-φd	H	
800Lb	2	50	292	165	127	92	36	6.4	8-19	310	
	2 1/2	65	330	190	149	105	29		8-22	230	
	3	80	356	210	168	127	32		8-22	255	
	4	100	432	273	216	157	38		8-25	295	
	5	125	508	330	266.5	186	45		8-29	310	
	6	150	559	355.5	292	216	47.5		12-29	365	
	8	200	660	419.5	349	270	56		12-32	420	
	10	250	787	508	432	324	63.57		16-35	505	
	12	300	838	559	489	381	66.5		20-35	545	
	14	350	889	603.5	527	413	70		20-38	600	
	16	400	991	686	603	470	76.5		20-41	650	

主要外形尺寸及连接尺寸 Key external dimensions and connection dimensions **JIS-H44H (Y, W) -10K, 20K**

公称直径DN		主要尺寸(mm)									
mm	in	d	L	D	D1	D2	b	f	H	Z-φd	
40	1 1/2	38	165	140	105	85	16	2	145	4-φ19	
50	2	51	203	155	120	100	16	2	165	4-φ19	
65	2 1/2	64	216	175	140	120	18	2	175	4-φ19	
80	3	76	241	185	150	130	18	2	185	8-φ19	
100	4	102	292	210	175	155	18	2	215	8-φ19	
125	5	127	330	250	210	185	20	2	240	8-φ23	
150	6	154	356	280	240	215	22	2	325	8-φ23	
200	8	203	495	330	290	265	22	2	383	12-φ23	
250	10	254	622	400	355	325	24	2	430	12-φ25	
300	12	305	698	445	400	370	24	2	490	16-φ25	
<b>20K</b>											
40	1 1/2	38	241	140	105	85	22	2	155	4-φ19	
50	2	51	267	155	120	100	22	2	185	8-φ19	
65	2 1/2	64	292	175	140	120	24	2	200	8-φ19	
80	3	76	318	200	160	135	26	2	220	8-φ23	
100	4	102	356	235	185	160	28	2	240	8-φ23	
125	5	127	400	270	225	195	30	2	270	8-φ23	
150	6	152	444	305	261	230	32	2	346	12-φ25	
200	8	203	533	350	305	275	34	2	412	12-φ25	
250	10	254	622	430	380	345	38	2	440	12-φ27	
300	12	305	711	480	430	395	40	3	530	16-φ27	

注：如法兰密封面采用凸面以外的型式，请在订货时注明。

Note: Please specify in your purchase order if flange sealing face uses types other than convex.

01000000000000000000