



主要外形尺寸及连接尺寸 Key external dimensions and connection dimensions J41H (Y, W)

规格 Class	公称通径(DN) Nominal through diameter		J41H外形尺寸								
	in	mm	L	D	D1	D2	b	f	Z-ød	H(全开)	W
150Lb	1/2	15	188	89	66.5	35	32	1.6	4-16	241	125
	3/4	20	117	98	70	43	13	1.6	4-16	241	125
	1	25	127	108	79.5	51	15	1.6	4-16	242	125
	1 1/4	32	140	117	89	63	16	1.6	4-16	280	160
	1 1/2	40	165	127	98.5	73	18	1.6	4-16	283	160
	2	50	203	152	120.5	92	20	1.6	4-19	368	200
	2 1/2	65	216	178	139.5	105	23	1.6	4-19	387	200
	3	80	241	190	152.5	127	24	1.6	4-19	411	230
	4	100	292	229	190.5	157	24	1.6	8-19	454	250
	5	125	356	254	216	186	24	1.6	8-22	455	355
	6	150	406	279	241.5	216	26	1.6	8-22	541	355
	8	200	495	343	298.5	270	29	1.6	8-22	651	450
	10	250	622	406	362	321	31	1.6	12-25	800	450
	12	300	698	483	432	381	32	1.6	12-25	1231	500
	14	350	787	533	476.5	413	35	1.6	12-29	1450	600
	16	400	914	597	539.5	470	37	1.6	16-29	1645	600

注：法兰密封面采用凸面以外的形式，请在订货时注明。

Note: Please specify in your purchase order if flange facing face one types other than convex.

API 598 标准

主要外形尺寸及连接尺寸 Key external dimensions and connection dimensions J41H (Y, W)

规格 Class	公称通径(DN) Nominal through diameter		凸面法兰(RF)主要连接尺寸 Key connection dimension of convex flange (RF)						J41H外形尺寸			
	in	mm	L	D	D1	D2	b	f	Z-ød	H(全开)	W	
300Lb	1/2	15	152	95	66.5	35	15	1.6	4-16	241	125	
	3/4	20	178	117	82.5	43	16	1.6	4-19	241	125	
	1	25	203	124	89	51	18	1.6	4-19	283	160	
	1 1/4	32	216	133	98.5	63	19	1.6	4-19	320	200	
	1 1/2	40	229	156	114.5	73	21	1.6	4-22	322	200	
	2	50	267	165	127	92	23	1.6	8-19	399	200	
	2 1/2	65	292	190.5	149	105	26	1.6	8-22	438	250	
	3	80	318	210	168.5	127	29	1.6	8-22	464	280	
	4	100	356	254	200	157	32	1.6	8-22	565	355	
	5	125	400	279	235	186	35	1.6	8-22	614	400	
	6	150	444	318	270	216	37	1.6	12-22	717	450	
	8	200	559	381	330	270	42	1.6	12-25	930	500	
	10	250	622	444.5	387.5	324	47.7	1.6	16-29	1012	450	
	12	300	711	520.7	451	381	50.8	1.6	13-32	1231	500	
	600Lb	2	50	292	165	127	92	26	6.4	8-19	430	250
		2 1/2	65	330	190	149	105	29	6.4	8-22	480	300
3		80	356	210	188	127	32	6.4	8-22	530	350	
4		100	432	273	216	157	38	6.4	8-25	650	400	
5		125	508	330	266.5	186	45	6.4	8-29	750	450	
6		150	559	356	292	216	48	6.4	12-29	850	560	
8		200	660	419	349	270	56	6.4	12-32	1050	640	

API 598 标准